

Outdoor cooling unit



Description

Order Number:	571511201
Brand Name:	Compact Outdoor
Colour:	RAL 7035
Housing Material:	Mild steel, powder coated
Ingress Protection:	IP 56 / Type 12, 3, 3R, 4
Included:	With enclosure heater and aluminium filter
Approvals:	CE, cURus, cULus
UL File Number:	cURus (SA32278), cULus (E498756)

Technical Data

Cooling capacity L35L35 (EN14511-3):	1500 W @ 50 Hz 1500 W @ 60 Hz
Cooling capacity L35L50 (EN14511-3):	1250 W @ 50 Hz 1280 W @ 60 Hz
Enclosure heater:	1000 W
Compressor type:	Reciprocating compressor
Refrigerant / GWP:	R134a / 1430
Refrigerant charge:	400 g / 14.1 oz
High / low Pressure:	26 / 6 bar 383 / 88 psig
Operating Temperature Range:	-40°C - 55°C
Air flow volume (system / unimpeded):	Ambient air circuit: 655 / 1200 m³/h Cabinet air circuit: 400 / 550 m³/h
Mounting:	Wall mounted
Dimensions A x B x C (D+E):	1,150 x 395 x 270 mm
Weight:	50 kg
Voltage / Frequency:	120 V ~ 50/60 Hz
UL Voltage / Frequency:	115 V ~ 60 Hz
Current L35L35:	10.8 A
Starting current:	32 A
Max. current:	14.2 A
Nominal power L35L35:	1.07 kW
Max. power:	1.30 kW
Fuse:	25 A (T)
Short-circuit current rating:	5 kA
Connection:	Connection terminal block

Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).

> [Overview Product Group COMPACT OUTDOOR - cooling units NEMA / Type 4X](#)

3/4

Order Information

Box dimensions	1,190 x 443 x 310 mm
Gross weight	53 kg
Taric code	84158200