


## Cabinet cooling unit



### Description

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|----------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Order Number:</b>       | 851500001                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>Brand Name:</b>         | SLIMLINE PRO                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| <b>Colour:</b>             | RAL 7035                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |
| <b>Housing Material:</b>   | Mild steel, powder coated                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| <b>Ingress Protection:</b> | IP 55 / Type 12                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
| <b>Approvals:</b>          | CE, cURus, cULus                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
| <b>Accessories:</b>        | <div>  <a href="#">Gasket Kit Type 4</a> </div> <div>  <a href="#">Washable Aluminium Filter 8515/20/25</a> </div> <div>  <a href="#">Cold Air Outlet Duct 8515/20/25</a> </div> <div>  <a href="#">Vibration Protection Kit 2</a> </div> |

## Technical Data

|                                              |                                                                            |
|----------------------------------------------|----------------------------------------------------------------------------|
| <b>Cooling capacity L35L35 (EN14511-3):</b>  | 1500 W @ 50 Hz<br>1500 W @ 60 Hz                                           |
| <b>Cooling capacity L35L50 (EN14511-3):</b>  | 1300 W @ 50 Hz<br>1300 W @ 60 Hz                                           |
| <b>EER L35L35:</b>                           | 2.17                                                                       |
| <b>Compressor type:</b>                      | Rotary piston                                                              |
| <b>Refrigerant / GWP:</b>                    | R134a / 1430                                                               |
| <b>Refrigerant charge:</b>                   | 320 g / 11.3 oz                                                            |
| <b>High / low Pressure:</b>                  | 30 / 6 bar<br>435 / 87 psi                                                 |
| <b>Operating Temperature Range:</b>          | 10°C - 60°C                                                                |
| <b>UL temperature range:</b>                 | 10°C - 60°C                                                                |
| <b>Air flow volume (system / unimpeded):</b> | Ambient air circuit: 550 / 850 m³/h<br>Cabinet air circuit: 500 / 850 m³/h |
| <b>Mounting:</b>                             | Wall mounted / recessed                                                    |
| <b>Dimensions A x B x C (D+E):</b>           | 1,350 x 395 x 210 (55+155) mm                                              |
| <b>Weight:</b>                               | 41 kg                                                                      |
| <b>Voltage / Frequency:</b>                  | 230 V ~ 50/60 Hz                                                           |
| <b>UL Voltage / Frequency:</b>               | 230 V ~ 60 Hz                                                              |
| <b>Current L35L35:</b>                       | 2.9 A                                                                      |
| <b>Starting current:</b>                     | 16 A                                                                       |
| <b>Max. current:</b>                         | 4.7 A                                                                      |
| <b>Nominal power L35L35:</b>                 | 690 W @ 50 Hz<br>700 W @ 60 Hz                                             |
| <b>Max. power:</b>                           | 1.1 kW                                                                     |
| <b>Fuse:</b>                                 | 15 A (T)                                                                   |
| <b>Max circuit ampacity:</b>                 | 15 A                                                                       |
| <b>Short-circuit current rating:</b>         | 5 kA                                                                       |
| <b>Rated current compressor:</b>             | 2.5 A                                                                      |

**Full load current fans:**

0.7 A

**Connection:**


4 pole terminal block for power  
5 pole terminal block for signals  
3 pole terminal block for RS 485

Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).


> [Overview Product Group SLIMLINE PRO - cooling units in a new design](#)

### Performance graph:



[click image to enlarge](#)

### Cut Out Dimension:



[click image to enlarge](#)

## Order Information

|                       |                     |
|-----------------------|---------------------|
| <b>Box dimensions</b> | 1442 x 495 x 242 mm |
| <b>Gross weight</b>   | 46.5 Kg             |
| <b>Taric code</b>     | 84158200            |