

Air / Water Heat Exchanger



Description

Order Number:	2125100
Brand Name:	SLIMLINE HEX
Colour:	RAL 7035
Housing Material:	Mild steel, powder coated
Ingress Protection:	IP 54
Note:	With Solenoid valve
Approvals:	CE

Technical Data

Cooling capacity L35W10 (200 l/h):	2500 W
Cooling capacity L35W10 (500 l/h):	3.15 kW (only w/o water flow regulator)
Coolant:	Water, light oils or similar
Operating Temperature Range:	1°C - 72°C
Air flow volume (system / unimpeded):	530 / 1300 m³/h
Mounting:	Wall mounted / internal
Dimensions A x B x C (D+E):	936 x 262 x 146.5 mm
Weight:	18 kg
Voltage / Frequency:	120 V ~ 60 Hz
Starting current:	3 A
Max. current:	1.7 A
Max. power:	200 W
Pressure water circuit:	10 bar
Water connection:	Rp 1/4" - inside thread with 2 connectors for pipe internal diameter of 10mm
Fuse:	5 A (T)
Connection:	Connection terminals


Please click on the graphics to download.

More CAD drawings can be found under [Product Download](#).

> [Overview Product Group SLIMLINE HEX - compact air/water heat exchangers](#)


Performance graph:

ΔT = Temperature difference between air intake and cooling
P = Cooling capacity




[click image to enlarge](#)

Air flow:



[click image to enlarge](#)

Cut Out Dimension:



[click image to enlarge](#)